

## TBL 25



[Accessories](#) [Docs](#) [Certificates](#) [Technical Detail](#)

<b>Product Code:</b>	8000099066
<b>Color Description:</b>	Blue
<b>Voltage V (IEC 60947-7-1):</b>	1000
<b>Current A (IEC 60947-7-1):</b>	101
<b>Impulse Voltage kV:</b>	8
<b>Cross section mm<sup>2</sup>:</b>	25
<b>Width mm:</b>	13,6
<b>Length mm:</b>	49,5
<b>Height mm MR35x7,5:</b>	61
<b>Height mm MR35x15:</b>	68,5
<b>Single Conductor Cross-Sectional Spacing min mm<sup>2</sup>:</b>	0.5
<b>Single Conductor Cross-Sectional Spacing max mm<sup>2</sup>:</b>	16
<b>Multi-Conductor Cross-Sectional Spacing min mm<sup>2</sup>:</b>	0.5
<b>Multi-Conductor Cross-Sectional Spacing max mm<sup>2</sup>:</b>	25
<b>AWG Section Range:</b>	20-4 AWG
<b>Cable Stripping Length mm:</b>	12.3
<b>Box Quantity:</b>	50
<b>Insulation Material:</b>	PA
<b>Tightening Torque N:</b>	2,5
<b>Crimping Tip:</b>	M5
<b>Screwdriver:</b>	1.0x5.5