



## FDT 4 L (110-220 VAC)

### Technical detail

<b>Product code:</b>	8003099518
<b>Color Definition:</b>	Gray
<b>Connection Type:</b>	Screw
<b>In and Out Type:</b>	1 In 1 Out
<b>Current A (IEC 60947-7-1):</b>	6,3
<b>Cross-Section mm<sup>2</sup>:</b>	4
<b>Width mm:</b>	8
<b>Length mm:</b>	72,5
<b>Height mm MR35x7,5:</b>	55,6
<b>Height mm MR35x15:</b>	63,1
<b>Solid Conductor Cross-Section min mm<sup>2</sup>:</b>	0.5
<b>Solid Conductor Cross-Section max mm<sup>2</sup>:</b>	4
<b>Stranded Conductor Cross-Section:</b>	0.5
<b>Stranded Conductor Cross-Section max mm<sup>2</sup>:</b>	4
<b>AWG Cross-Section:</b>	20-12 AWG
<b>Stripping Length mm:</b>	12
<b>Packing Quantity:</b>	25
<b>Insulation Material:</b>	PA
<b>Tightening Torque N:</b>	0,5
<b>Clamping Screw:</b>	M3
<b>Screw Driver:</b>	0,5x3,0
<b>Cross-Connection Type:</b>	Screw