

TO-JTK

Insulated Ring Terminals

Wire range: 0.5~1.5mm² (A.W.G. 22~16): I_{max}=19A

Item No	Stud size	Dimension(mm)						Color
		d2	B	L	F	H	Dφ	
RV1.25-3.2	#4	3.2	5.7	17.8	4.95	10.0	4.3	Red
RVS1.25-3.5	#6	3.7	5.7	17.8	4.95			
RVM1.25-3.5	#6	3.7	6.6	20.1	6.3			
RVL1.25-3.5	#6	3.7	8.0	21.5	7.0			
RVS1.25-4	#8	4.3	6.6	20.1	6.3			
RVL1.25-4	#8	4.3	8.0	21.5	7.0			
RVS1.25-5	#10	5.3	8.0	21.5	7.0			
RVL1.25-5	#10	5.3	9.8	23.0	8.5			
RVS1.25-6	1/4	6.4	9.8	23.0	8.5			
RV1.25-6	1/4	6.4	11.6	27.5	11.1			
RV1.25-8	5/16	8.4	11.6	27.5	11.1			
RV1.25-10	3/8	10.5	13.6	31.6	13.9			
RV1.25-12	1/2	13.0	19.2	36.0	16.5			



Material

Insulation: PVC

Terminal Body: Copper Plating: Tin

