

TO-JTK

Insulated Ring Terminals

Wire range: 1.5~2.5mm² (A.W.G. 16~14) : I_{max}=27A

| Item No | Stud size | Dimension(mm) | | | | | | Color |
|----------|-----------|---------------|------|------|------|------|-----|-------|
| | | d2 | B | L | F | H | Dφ | |
| RV2-3.2 | #4 | 3.2 | 6.6 | 17.8 | 4.3 | 10.0 | 4.9 | Blue |
| RVS2-3.5 | #6 | 3.7 | 6.6 | 17.8 | 4.3 | | | |
| RVM2-3.5 | #6 | 3.7 | 6.6 | 21.0 | 7.0 | | | |
| RVL2-3.5 | #6 | 3.7 | 8.5 | 22.5 | 7.75 | | | |
| RVS2-4 | #8 | 4.3 | 6.6 | 21.0 | 7.0 | | | |
| RVL2-4 | #8 | 4.3 | 8.5 | 22.5 | 7.75 | | | |
| RVS2-5 | #10 | 5.3 | 8.5 | 22.5 | 7.75 | | | |
| RVL2-5 | #10 | 5.3 | 9.5 | 22.5 | 7.25 | | | |
| RV2-6 | 1/4 | 6.4 | 12.0 | 27.6 | 11.0 | | | |
| RV2-8 | 5/16 | 8.4 | 12.0 | 27.6 | 11.0 | | | |
| RV2-10 | 3/8 | 10.5 | 13.6 | 30.2 | 13.9 | | | |
| RV2-12 | 1/2 | 13.0 | 19.2 | 36.5 | 16.5 | | | |



Material

Insulation: PVC

Terminal Body: Copper Plating: Tin

