



## TBL 2.5

[Accessories](#) [Docs](#) [Certificates](#) [Technical Detail](#)

<b>Product Code:</b>	8000099006
<b>Color Description:</b>	Blue
<b>Voltage V (IEC 60947-7-1):</b>	500
<b>Current A (IEC 60947-7-1):</b>	24
<b>Impulse Voltage kV:</b>	6
<b>Cross section mm<sup>2</sup>:</b>	2,5
<b>Width mm:</b>	6
<b>Length mm:</b>	45,3
<b>Height mm MR35x7,5:</b>	47,4
<b>Height mm MR35x15:</b>	54,9
<b>Single Conductor Cross-Sectional Spacing min mm<sup>2</sup>:</b>	0.5
<b>Single Conductor Cross-Sectional Spacing max mm<sup>2</sup>:</b>	4
<b>Multi-Conductor Cross-Sectional Spacing min mm<sup>2</sup>:</b>	0.5
<b>Multi-Conductor Cross-Sectional Spacing max mm<sup>2</sup>:</b>	4
<b>AWG Section Range:</b>	20-12 AWG
<b>Cable Stripping Length mm:</b>	10
<b>Box Quantity:</b>	100
<b>Insulation Material:</b>	PA
<b>Tightening Torque N:</b>	0,6
<b>Crimping Tip:</b>	M2.5
<b>Screwdriver:</b>	0.5x3.0