

- A cable chain is a mechanical system designed to protect, carry and guide cables (power, control, data or fiber optics) and hoses (hydraulic or pneumatic) in dynamic motion applications



# J15BF.1.N

## SEMI-CLOSED INTERIOR OPENING PLASTIC CARRIER CHAIN CONVEYORS MACHINE CABLE CHAIN

P/N#	Hi	Bi	Ha	Ba	Bending Radius	Bracket P/N #
J15BF.1.15N	15	15	20	23	R28	J15BF.1.15N-XJT
J15BF.1.20N	15	20	20	28	R28 R38	J15BF.1.20N-XJT
J15BF.1.30N	15	30	20	38	R28 R38 R48	J15BF.1.30N-XJT
J15BF.1.40N	15	40	20	48	R28 R38 R48	J15BF.1.40N-XJT
J15BF.1.50N	15	50	20	58	R28 R38 R48	J15BF.1.50N-XJT
<b>BASIC TECHNICAL DATA</b>						
<b>PITCH=20MM, PER METER=50 LINKS, LENGTH OF CHAIN=S/2+K, S=Stroke</b>						



## J30F.1.S

### CLOSED TYPE CABLE DRAG CHAIN, JFLO J30F SERIES, CNC MACHINE CABLE CARRIER

P/N#	Hi	Bi	Ha	Ba	Bending Radius	Bracket P/N #
J30F.1.38S	30	38	45	54	R75 R100 R125 R150	J30F.1.38S-FJT
J30F.1.50S	30	50	45	66		J30F.1.50S-FJT
J30F.1.57S	30	57	45	73		J30F.1.57S-FJT
J30F.1.60S	30	60	45	76		J30F.1.60S-FJT
J30F.1.75S	30	75	45	91		J30F.1.75S-FJT
J30F.1.77S	30	77	45	93		J30F.1.77S-FJT
J30F.1.100S	30	100	45	116		J30F.1.100S-FJT
<b>BASIC TECHNICAL DATA</b>						
PITCH=46MM, PER METER=22 LINKS, LENGTH OF CHAIN=S/2+K, S=Stroke						



# H35Q

## PLASTIC CABLE CHAIN OPENING H35 SERIES, DRAG CABLE CHAIN FACTOR

系列号 Series No.	内高 Hi	内宽 Bi	外高 Ha	外宽 Ba	款式 Styles	弯曲半径 Bending radius R	固定接头类型及参数 Bracket type and parameters								
							可配接头类型 Applicable bracket type	孔径 Bore diameter Φ1	孔距 (mm)hole distance						代号 No.
									A	B	C	D	E	F	
H35Q.1.50S	35	50	55	76	Q.S	75,100,125, 150,200,300	F-Q	6	24	66	84.5	26	16	78	H35Q.1.50S-FJT
H35Q.1.60S	35	60	55	86	Q.S		F-Q	6	24	76	84.5	26	16	88	H35Q.1.60S-FJT
H35Q.1.75S	35	75	55	101	Q.S		F-Q	6	24	91	84.5	26	16	103	H35Q.1.75S-FJT
H35Q.1.90S	35	90	55	116	Q.S		F-Q	6	24	106	84.5	26	16	118	H35Q.1.90S-FJT
H35Q.1.100S	35	100	55	126	Q.S		F-Q	6	24	116	84.5	26	16	128	H35Q.1.100S-FJT
H35Q.1.117S	35	117	55	143	Q.S		F-Q	6	24	133	84.5	26	16	145	H35Q.1.117S-FJT
H35Q.1.125S	35	125	55	151	Q.S		F-Q	6	24	141	84.5	26	16	153	H35Q.1.125S-FJT
H35Q.1.130S	35	130	55	156	Q.S		F-Q	6	24	146	84.5	26	16	158	H35Q.1.130S-FJT
H35Q.1.150S	35	150	55	176	Q.S		F-Q	6	24	166	84.5	26	16	178	H35Q.1.150S-FJT
H35Q.1.154S	35	154	55	180	Q.S		F-Q	6	24	170	84.5	26	16	182	H35Q.1.154S-FJT
H35Q.1.175S	35	175	55	201	Q.S		F-Q	6	24	191	84.5	26	16	203	H35Q.1.175S-FJT
H35Q.1.200S	35	200	55	226	Q.S		F-Q	6	24	216	84.5	26	16	228	H35Q.1.200S-FJT
H35Q.1.250S	35	250	55	276	Q.S		F-Q	6	24	266	84.5	26	16	278	H35Q.1.250S-FJT
H35Q.1.300S	35	300	55	326	Q.S		F-Q	6	24	316	84.5	26	16	328	H35Q.1.300S-FJT

注：S 表示两侧可打开  
Note: S indicates that the both side open

### 固定接头类型及参数 Fix bracket type and parameters ( 见表格 See table)

